



Miniature circuit breaker

FB3-125 EVO C 3P 80A

Order code: FB3C3080

Technical specifications

| Main | |
|---|---|
| Standard | IEC/EN 60898, IEC/EN 60947-2 |
| Series | FB3-125 EVO |
| Type | Miniature circuit breaker |
| Number of poles | 3P |
| Number of protected poles | 3 |
| Rated current I_n , A | 80 |
| Network type | AC |
| Rated frequency f , Hz | 50/60 |
| Trip unit technology | thermal-magnetic |
| Selectivity class | 3 |
| Tripping characteristics | C |
| Utilisation category | category A conforming to EN/IEC 60947-2 |
| Rated voltage U_n , V | 230/400 |
| Rated breaking capacity I_{cs} , A | 15 000 |
| Rated voltage of the insulation U_i , V | 500 |
| Rated impulse withstand voltage U_{imp} , kV | 4 |
| Contact position indicator | yes |
| Control type | toggle |
| Mounting mode | clip-on |
| DIN rail mounting | TN 35 |
| Height, mm | 90 |
| Width, mm | 81 |
| Depth, mm | 78 |
| Weight, kg | 0.660 |
| Mechanical service life (cycles) | 20 000 |
| Electrical service life (cycles) | 10 000 |
| Cross-section of connecting conductors, mm ² | up to 50 |
| Connecting of busbar | PIN |
| Connecting of additional devices | yes |
| Bolt tensioning torque, Nm | 3.5 |
| Release time, s | ≤0.1 |
| Sealing option ON/OFF | yes |

| Environment | |
|---------------------------------|--------------------------------|
| Protection class | IP20 conforming to IEC 60529 |
| Pollution degree | 3 conforming to EN/IEC 60947-2 |
| Altitude above sea level, m | 0...2 000 |
| Operating temperature range, °C | -25...+55 |
| Storage temperature range, °C | -25...+70 |
| Warranty | 5 years |