



**Miniature circuit breaker**  
**FB3-125 EVO D 3P 80A**  
 Order code: FB3D3080

**Technical specifications**

Main	
Standard	IEC/EN 60898, IEC/EN 60947-2
Series	FB3-125 EVO
Type	Miniature circuit breaker
Number of poles	3P
Number of protected poles	3
Rated current $I_n$ , A	80
Network type	AC
Rated frequency $f$ , Hz	50/60
Trip unit technology	thermal-magnetic
Selectivity class	3
Tripping characteristics	D
Utilisation category	category A conforming to EN/IEC 60947-2
Rated voltage $U_n$ , V	230/400
Rated breaking capacity $I_{cs}$ , A	15 000
Rated voltage of the insulation $U_i$ , V	500
Rated impulse withstand voltage $U_{imp}$ , kV	4
Contact position indicator	yes
Control type	toggle
Mounting mode	clip-on
DIN rail mounting	TN 35
Height, mm	90
Width, mm	81
Depth, mm	78
Weight, kg	0.660
Mechanical service life (cycles)	20 000
Electrical service life (cycles)	10 000
Cross-section of connecting conductors, mm <sup>2</sup>	up to 50
Connecting of busbar	PIN
Connecting of additional devices	yes
Bolt tensioning torque, Nm	3.5
Release time, s	≤0.1
Sealing option ON/OFF	yes

Environment	
Protection class	IP20 conforming to IEC 60529
Pollution degree	3 conforming to EN/IEC 60947-2
Altitude above sea level, m	0...2 000
Operating temperature range, °C	-25...+55
Storage temperature range, °C	-25...+70
Warranty	5 years